

- WiFi
- 2 SIP Lines
- HD Voice
- 132 \* 58 Graphic Character Dot Matrix with Backlight LCD



## C2W

C2W WiFi SIP Phone is a multi-access network, easy to deploy and operate desktop office phone for enterprise users, which features excellent sound quality, elegant and smart design. It supports 2 SIP accounts, which combines economical, practical and excellent performance dual advantage in one. It is an entry-level IP Phone specially designed for business office, suitable for enterprise unified communications.

### Basic Functions

- 132 \* 58 graphic character dot matrix with backlight LCD
- 2 SIP accounts
- Call Forward, Call Transfer, Call Waiting, Hotline, Call Hold,
- Auto Answer, Caller ID, Redial, Mute, DND
- Local 3-Way Conferencing, Speed Dial, Voice Mail
- Phone Book (1000)
- Direct IP call without SIP proxy
- Black list, white list
- Dialed/received/missed call (each 200)
- Call Center Headsets mode

### PBX Features

- Intercom, Paging, Call pickup, Call park
- Anonymous call, Anonymous call rejection
- Hold on music, Conference Call, Group Listening, Group Pickup, DND&Call forward state synchronization
- Call Recording

### Advanced Features

- LDAP
- Microsoft active directory server
- XML remote phonebook

### Audio Features

- 8 own ring tone, 2 custom ring tone article
- 8 volume adjustable + Mute mode
- Narrowband codec: G.711(A/μ), G.729A/B/AB, G.726, iLBC
- Wideband codec: G.722, L16
- Support VAD, CNG, AEC, PLC, AJB AGC
- Full-duplex speakerphone with AEC

### Network Features

- LAN / PC: support bridging mode
- OpenVPN client support
- SIP connection mode: Proxy mode, and P2P mode
- Support DNS SRV (RFC3263)
- NAT transverse: STUN mode
- DTMF: In-band, RFC2833, SIP INFO
- Support QoS
- HTTP / HTTPS web server
- Package tracing export
- System log

### WiFi Features

- Support IEEE 802.11b/g/n
- Enhanced support for IEEE 802.11e QoS
- Support APA, APA2, IEEE802.11i (WPA, WPA2)

### Safety Features

- VLAN, LLDP, IEEE802.1X
- Support TLS
- Support HTTPS
- SRTP (RFC3711)
- Digest authentication using MD5/MD5-sess
- AES encryption for configuration file
- Support phone lock, the administrator / user rating mode

### Configuration

- PnP configuration: based on the server implementation
- Manual configuration: Web, Keypad
- Batch deployment: HTTP/FTP/TFTP/RPS/DHCP Option 66

### Physical Features

- Power Interface: DC 5V-1A
- 2 RJ45 10/100M adaptive Ethernet ports
- 1 RJ9 headphone jack, 1 RJ9 handset jack
- 1 status indicator, 3 soft keys, 5 navigation keys
- 2 line keys, 2 volume keys
- 7 function keys (menu, cancel, voicemail, mute, headphone, Redial, hands-free)
- Wall mountable
- Operation Temperature: -10 ~ 50° C
- Operating humidity: 10 ~ 90%

### Package

- Qty/CTN: 10 pieces
- G.W/CTN: 11KG
- Box Size: 280mm\*210mm\*78mm
- Carton Meas: 425mm \*415mm \*300mm

### Multi-languages

English, German, French, Italian, Spanish, Turkish, Polish, Russian, Chinese Simplified, Chinese Traditional, Portuguese, Arabic, Hebrew

### For more information, please contact Us

Copyright © 2005 – 2012 VOPTel Technology Co., Ltd. All rights reserved.

VOPTech is a registered trademark of VOPTel Technology Co., Ltd and affiliates in China, and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, in this document are legally protected trademarks of VOPTel Technology Co., Ltd.

Address: R201, Deyefeng Business Center, No. 1035, Gongyuan Road, Baoan District, Shenzhen, P.R.China

Tel: 86 755 27668969

Sale Email: sales@VOPTech.com