

VPX-100 IP Phone System For small and large business

No User License Fee
All Standard PBX Features
Many Advanced PBX Features
Desktop Call Management
Firewall
Intrusion Detection
Enhanced Security Policies
Support Program
Remote Backup Service
Disaster Recovery



VPX-100 IP Phone system

The VPX-100 IP Phone System is an ideal solution for business with up to 500 extensions and up to 80 concurrent calls. Adopting the innovative modular design, it is very convenient to increase telephony ports to expand the system. VPX-100 supports industry standard SIP trunks, analog PSTN trunks (FXO Module), analog stations (FXS Module), mobile GSM trunks (GSM Module), as well as digital trunks (PRI/BRI Module).

VPX-100 is a next-generation Hybrid IP PBX System designed and optimized for today's business telecommunication needs. VPX-100 is an affordable, scalable, interoperable, secure and reliable solution which provides not only traditional PBX features such as Automated Attendant and Voicemail, but also many advanced features including Remote Extensions, Remote Office Connection, Conference Bridge, Call Recording, Call Detail Records (CDR), Automatic Call Distribution (ACD), Unified Messaging (Voicemail to Email), and many more features.

Technical Data

Benefits & Features:

- HD Voice Codec G.722 for perfect voice quality
- Fax to Email/Email to Fax
- Voicemail to Email
- Console Port for easy management
- USB Port for expanded storage or 3G network connectivity
- Hardware Echo Cancellation module for great and smooth communication

Telephony Configuration

Module \ slot	slot 1	slot 2
4FXO	√	√
4FXS	√	√
2FXO&2FXS	√	√
2GSM	√	√
4GSM	√	√
1PRI	√	×
4PRI	√	×

BRI is available on Slot 2 only

System Specifications

Call Features

- Call Back/Call Forward/Call Group/Call Hold
- Call Paging and Intercom/Call Park/Call Pickup
- Call Queue/Call Recording/Call Routing/Blind Transfer/Attended Transfer/Call Waiting/Caller ID
- Dial by Name/Music On Hold/Transfer
- 3-Way Conference/Video Call

PBX Features

- Black List/BLF (Busy Lamp Field)
- CDR (Call Detailed Record)
- Conference Room (3 Rooms)/Call Monitoring
- DID (Direct Inward Dialing Number)
- DISA (Direct Inward System Access)
- Distinctive Ringtone/DND (Do Not Disturb)
- DNIS (Dialed Number Identification Service)
- Feature Codes/Follow Me
- IVR (Interactive Voice Responses)
- Mobility Extension/Multi-Language Prompts
- Multi-Language GUI/One Touch Recording
- Phone Book/Phone Provisioning/Pin Set
- Record File
- Download/Ringgroup/SIP Register with DP/TCP/TLS
- SIP Trunk/Skype for SIP/Smart DID
- Speed Dial/Spy/SRTP (Secure Realtime Transport Protocol)
- T.38 Fax (Pass-through)
- Time Based Rule/Virtual Fax
- Voicemail & Voicemail to Email

System Capacities

- 80 Concurrent Calls
- Up to 500 IP Phone Registers/Extensions
- Recording: 2,500,000 mins (.gsm);270,000 mins (.wav)
- Voicemail: 2,500,000 mins (.gsm);270,000 mins (.wav)

Codecs & Protocols

- Audio Codecs: G.722/G.711-Ulaw/G.711-Alaw/G.726/G.729/GSM/SPEEX
- Video Codecs: H.261/H.263/H.263+/H.264
- Protocols: SIP (RFC3261)/IAX2
- DTMF: RFC2833/SIP INFO/In-Band

Network Features

- DDNS Client
- DHCP Server
- IPv4/IPv6/IEEE802.1Q
- IP Assignment (PPPoE/DHCP/Static)
- SNMP v1/v2
- TR069
- Static Route Table
- Trouble Shooting (Ping/Traceroute)
- VPN Client (N2N/L2TP/PPTP/OpenVPN)
- VPN Server (PPTP/L2TP/OpenVPN, Up to 10 Users)

Security Features

- Refuse SIP Register DoS
- Refuse Abort Invite DoS
- Refuse SSH Login DoS
- Firewall

Logs

- PBX Log/Web Access Log/PBX Debug Log

Hardware Interfaces

- 1 Power Interface
- 1 Power Switch
- 2 Ethernet Interfaces (10/100/1000Mbps)
- 1 VGA Interface
- 2 Audio Interfaces
- 2 USB Interfaces
- 2 Interfaces for Optional
- Hardware Echo Cancellation Module
- 1 Interface for Optional UMTS Module
- 2 Slots for ZYCOO Standard Modules

Hardware Specifications

- CPU: DualCore 1.86 GHz ATOM
- SDRAM: DDR3 2GB
- Storage: 500GB HDD (default) or 32GB SSD (optional)
- Power Supply: AC 100~240V, 50/60Hz, 1.5A max.

Environment

- Working Temperature: 0 ~ 40°C
- Storage Temperature: -20 ~ 55°C
- Humidity: 5 ~ 95% Non-condensing

Packings

- Dimension: 500 × 310 × 90mm
- Weight/Unit: 4.5kg

For more information, please contact Us

Copyright © 2005 – 2012 VOPTEl Technology Co., Ltd. All rights reserved.

VOPTEch is a registered trademark of VOPTEl Technology Co., Ltd and affiliates in China, and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, in this document are legally protected trademarks of VOPTEl Technology Co., Ltd.

Address:R201, Deyefeng Business Center, No. 1035, Gongyuan Road, Baoan District, Shenzhen, P.R.China

Tel: 86 755 27668969

Sale Email: sales@VOPTEch.com